Benutzerinformation Sägeblatt

Dieses Sägeblatt ist in Übereinstimmung mit der EN 847-1 hergestellt. Diese Sicherheitshinweise für künftige Verwendung aufbewahren.

Sicherheitshinweise:

- Sägeblätter dürfen nur von ausgebildeten und erfahrenen Personen, die den Umgang damit beherrschen, benutzt werden.
- Zur Vermeidung von Verletzungen sind bei der Handhabung grundsätzlich Schutzhandschuhe zu tragen.
- Die auf dem Sägeblatt angegebene Höchstdrehzahl darf nicht überschritten werden.
- Kreissägeblätter, deren Körper gerissen sind, müssen ausgemustert werden (Instandsetzung ist nicht zulässig).
- Sägeblätter müssen so aufgespannt sein, dass sie sich beim Betreiben nicht lösen können.
- Befestigungsschrauben und -muttern müssen unter Verwendung geeigneter Montagewerkzeuge, mit dem vom Hersteller angegebenen Drehmoment angezogen werden.
- Das Verlängern von Schlüsseln oder die Verwendung von Schlagwerkzeugen zum Festziehen ist nicht zulässig.
- Die Spannflächen müssen von Verschmutzungen, Fett, Öl und Wasser gereinigt werden.
- Zum Einstellen des Bohrungsdurchmessers von Kreissägeblättern an den Spindeldurchmesser der Maschine dürfen nur fest eingebrachte Ringe, z.B. eingepresste oder durch Haftverbindung gehaltene Ringe, verwendet werden. Die Verwendung loser Ringe ist nicht zulässig.
- Das Nachschleifen (Schärfen) des Sägeblattes ist nur durch Fachpersonal zulässig, die die Anforderungen an Konstruktion und Gestaltung kennt und sich auf das erfordleriche Sicherheitsniveau versteht. Folgendes ist besonders zu beachten: Es ist sicherzustellen, dass die Anforderungen an das Auswuchten der Werkzeuge nach EN 847-1/5.2.3.2, erfüllt werden.
- Ersatzteile müssen den Festlegungen für die vom Hersteller gelieferten Originalteile entsprechen.

User information for saw blade

This saw blade is produced in agreement with the EN 847-1. Keep this safety instruction for future use.

Safety instructions:

- Saw blades may only be used by trained and skilled persons, who are sure in using them.
- Strictly wear protective gloves to avoid injuries.
- The maximum permissible speed indicated on the saw blade must not be exceeded.
- Cracked circular saw blades must be taken out of use (do not repair).
- Saw blades must be fixed carefully so that they cannot be unfasten during the operation.
- Fixing screws and nuts must be tightened by using suitable assembling tools (consider the tightening torque indicated by the manufacturer).
- Extension of wrenches or the use of impact tools/striking tools (e. g. hammer) to tighten the saw blade is not allowed.
- The surfaces of the saw blades and the flanges must be cleaned from contaminations, fat, oil and water.
- To adjust the bore diameter of circular saw blades to the spindle diameter of the machine, only firmly fitted rings, e.g. pressed-in rings or rings held in place by an adhesive connection, may be used. The use of loose rings is not permitted.
- The sharpening of the saw blade may only be carried out by specialised persons, who knows the requirements for construction and design and understands the required level of safety. Particularly take care of the following: Ensure that the requirements of balancing the tools will be fulfilled according to EN 847-1/5.2.3.2.
- Spare parts must comply with the specifications for original parts supplied by the manufacturer.

365155 – 02 01/2021