



# TECHNICAL SHEET

FA 40 900 20

**Designation:**

Work Positioning Twisted Rope Lanyard with Ring Adjuster

- Made up of 14mm diam polyamide twisted rope.
- Abrasion resistant thimble to protect the loops from being damaged by metallic contact.
- Spliced end is protected with a strong transparent covering sleeve.
- Colored tracer strand losing color to show that the lanyard is unfit for use.
- Breaking strength : 15 kN

**Connectors:**

1 screw-locking karabiner opening 17 mm, ref. FA5010117 and 1 snap hook opening 17mm FA5020217

Compliance: EN358: 2000

**Length :**

Maximum Length : 2 mtrs

**Materials:**

Lanyard: polyamide

Connectors: steel

Ring Adjuster: Forged alloy steel



**HS code**

56090090

**Carton Size/ Pieces**

71x33x21 / 25

**Unit Weight**

0,76 kg

**AET: N° 2345 Issue 1 Extension 14**

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering,  
Northamptonshire, NN16 8SD, United Kingdom.

**Article 11: GB07/73551**

SGS United Kingdom Ltd., N° 0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom



Maj.: 07/13

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

