


Geberit Mepla T-Stück reduziert



Verwendungszweck

- Verwendungsübersicht: Geberit Mepla

Eigenschaften

- Unverpresst undicht
- O-Ring aus EPDM
- Pressnippel mit transparenter Schutzkappe

Technische Daten

Werkstoff

PVDF

Artikel

Art.-Nr.	NPK-Nr.	DN	d, ø [mm]	d1, ø [mm]	d2, ø [mm]	L [cm]	L1 [cm]	Z [cm]	Z1 [cm]	Z2 [cm]
622.313.00.5	253.162	12 / 15 / 12	16	20	16	9.6	5.1	2.2	2.2	2.2
622.314.00.5	253.162	15 / 12 / 12	20	16	16	9.9	4.8	2.2	2.2	2.2
622.311.00.5	253.162	15 / 12 / 15	20	16	20	10.1	4.8	2.2	2.2	2.2
622.312.00.5	253.162	15 / 15 / 12	20	20	16	9.9	5.1	2.2	2.2	2.2
623.318.00.5	253.163	15 / 20 / 15	20	26	20	11.3	5.5	2.8	2.2	2.8
623.311.00.5	253.163	20 / 12 / 20	26	16	26	10	5.2	1.7	2.6	1.7
623.317.00.5	253.163	20 / 15 / 15	26	20	20	10.9	5.7	2.2	2.8	2.5
623.315.00.5	253.163	20 / 15 / 20	26	20	26	11	5.7	2.2	2.8	2.2
623.316.00.5	253.163	20 / 20 / 15	26	26	20	11.5	5.8	2.2	2.2	2.8
624.311.00.5	253.164	25 / 12 / 25	32	16	32	11.6	5.5	2	2.9	2
624.314.00.5	253.164	25 / 15 / 20	32	20	26	11.5	6	2.2	3.1	2.2
624.317.00.5	253.164	25 / 15 / 25	32	20	32	11.6	6	2	3.1	2
624.316.00.5	253.164	25 / 20 / 20	32	26	26	11.7	5.9	2.3	2.6	2.3
624.319.00.5	253.164	25 / 20 / 25	32	26	32	12.2	5.9	2.3	2.6	2.3
625.317.00.5	253.165	32 / 15 / 32	40	20	40	13.2	6.4	2.2	3.5	2.2
625.319.00.5	253.165	32 / 20 / 32	40	26	40	13.8	6.5	2.5	3.2	2.5
625.321.00.5	253.165	32 / 25 / 32	40	32	40	14.4	7.2	2.8	3.2	2.8
626.317.00.5	253.166	40 / 20 /	50	26	50	15.4	7.1	2.7	3.8	2.7

		40								
626.319.00.5	253.166	40 / 25 / 40	50	32	50	16	7.6	3	3.8	3
626.320.00.5	253.166	40 / 32 / 32	50	40	40	16.2	8.2	3.4	3.8	3.4
626.321.00.5	253.166	40 / 32 / 40	50	40	50	16.8	8.2	3.4	3.8	3.4
627.316.00.5	253.167	50 / 20 / 50	63	26	63	19.2	7.9	2.8	4.6	2.8
627.320.00.5	253.167	50 / 25 / 50	63	32	63	19.8	8.6	3.1	4.8	3.1
627.321.00.5	253.167	50 / 32 / 50	63	40	63	20.8	9.2	3.6	4.8	3.6
627.322.00.5	253.167	50 / 40 / 50	63	50	63	22	9.8	4.2	4.8	4.2
628.316.00.5	253.168	65 / 20 / 65	75	26	75	23.5	8.9	3.1	5.5	3.1
628.320.00.5	253.168	65 / 25 / 65	75	32	75	24	8.8	3.3	5	3.3
628.321.00.5	253.168	65 / 32 / 65	75	40	75	24.9	9.9	3.7	5.5	3.7
628.322.00.5	253.168	65 / 40 / 65	75	50	75	25.9	10.8	4.2	5.8	4.2
628.323.00.5	253.168	65 / 50 / 65	75	63	75	27.7	12.7	5.2	6	5.2