


Lindau LV

Méthode de fabrication	Needlefelt	ISO 2424
Aspect	Flat	ISO 2424
Largeur	200 cm, 400 cm	
Dossier	LV	ISO 2424
Composition velours	100% PP	
Poids velours	630 gr/m²	
Poids total	790 gr/m²	+/- 15% ISO 8543
Hauteur totale	4,5 mm	+15% / -10% ISO 1765
Évaluation de zone d'utilisation	Commercial 33, Areas with heavy use	EN ISO 10874
Classe de luxe	LC1	EN 1307
Résistant aux chaises à roulettes	Yes, permanent use	EN 985
Convient pour escaliers	Yes, incidental use	EN 1307
Solidité à la lumière	≥ 5	ISO 105-B02
Résistance au frottement (humide et sec)	≥ 4	ISO 105-X12
Résistance à l'eau	≥ 4	ISO 105-E01
Résistance dimensionnelle	Shrinkage ≤ 1,2 %	ISO 2551
	Extension ≤ 0,5 %	ISO 2551
Charge électrostatique	< 2kV	ISO 6356
Conductivité thermique	0,07 m².K/W	ISO 8302
Résistance au glissement	DS (> 0,30)	EN 13893
Classement feu	Cfl,s1	EN 13501-1
Prodis-ID (GuT)	E1146BAA	www.pro-dis.info
TÜV PROFICERT product	Certificate number: 70 710 5617-3	

Floorsymbols



Certificates



ISO 9001:2015-certified processes
 ISO 14001:2015-certified processes

2019-06-19

Vebe Floorcoverings b.v. products are to be installed in full accordance with Vebe installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Vebe products should only be used as floorcoverings. Note: Vebe Floorcoverings b.v. reserves the right to adapt this specification without giving prior notice. For the latest versions of the technical specifications, check our internet site.

In the area of office chairs we recommend to use mats made of polycarbonate. This extends the life of your carpet.

Laying: Fully glued with adhesive that withstands chair castors.

The producer reserves the right to change technical specifications. Due to variations in raw materials and production circumstances, the product may vary from batch to batch.